

TURF GRIP

PRIME

Turf Grip PRIME is a high viscosity polyurethane adhesive that is specially formulated to meet the stringent requirements of today's multi-use synthetic surfaces. It is a solvent-free, single-component, moisture-cured structural adhesive designed to bond all types of synthetic turf, including; putting greens, athletic fields, lawns, airport safety zones, public greenways, and play areas. **Turf Grip PRIME** is non-flammable, contains no solvents, bonds quickly and completely with moisture present in hot or cold weather conditions, and has a very low odor. It can be used for indoor and outdoor applications and can contribute to obtaining LEED® Credits. **Turf Grip PRIME** is easy to use and provides high initial tack and good green strength.

PHYSICAL PROPERTIES

WORKING TIME:	20 - 25 minutes
STRUCTURAL CURE:	24 hours
VISCOSITY @ 77°F:	75,000 – 100,000 cPs
APPLICATION TEMPERATURE:	40°F to 120°F (4°C to 49°C)
STORAGE TEMPERATURE RANGE:	65°F to 95°F (18°C to 35°C)
SHELF LIFE IN UNOPENED CONTAINER:	12 months from date of manufacture
EPA Method 24 VOC:	15.6 g/L

SUSTAINABILITY GUIDE

GREENGUARD® Children & Schools Certified

GREENGUARD® Indoor Air Quality Certified

- Contributes to *LEED®* and other green building rating system credits:
 - *LEED-NC* and *LEED-CI EQ Credits 3.2* and *4.1*, and *ID Credit 1.1-1.4*
 - *LEED for Schools EQ Credits 3.2* and *4*, and *ID Credit 1.1-1.4*
 - *LEED for Homes MR Credit 2.2 Environmentally Preferable Materials*
 - *LEED Core & Shell EQ Credit 4.1* and *ID Credit 1.1-1.4*
 - *LEED-EB MR Credit 3*
 - *CHPS® (Collaborative for High Performance Schools) EQ Credit 2.2*
 - *Green Guide for Health Care EQ Credit 4.1*
 - *NAHB Model Green Home Bldg Guidelines – Sect 7, Global Impact 7.1.3*



REGULATORY COMPLIANCE

- SCAQMD (South Coast Air Quality Management District), Rule 1168
- California Air District Regulations
- Ozone Transport Commission (OTC) model Rule for Adhesives and Sealants

TW TACC

56 Air Station Industrial Park
Rockland, MA 02370

Phone 1-800-503-6991 Fax 1-800-231-8222
info@itwtacc.com www.itwtacc.com

TURF GRIP PRIME™

Synthetic Turf Adhesive

DIRECTIONS

Surfaces should be clean, dry, and free from dirt, oil, grease, and other contaminants before applying adhesive. Spread an even coating of adhesive to the substrate. Apply with a 3/16" square trowel or glue box. When trowel applied, it maintains the ridges. Put the surfaces together. Apply even pressure over the surfaces. Full curing takes a minimum of 24 hours. Drying and curing time will vary with temperature and humidity.

STORAGE

Store in a dry place. Store out of direct sunlight in a cool, well-ventilated area. Avoid storing container directly on the floor or against an outside wall. Do not expose to temperatures below 65°F (18°C) and above 95°F (35°C). Do not allow contact with water or moisture. WATER CONTAMINATION WILL RENDER ADHESIVE UNUSABLE AND CAN CAUSE A CLOSED CONTAINER TO BULGE AND EVEN RUPTURE EXPLOSIVELY.

ATTENTION: Empty containers may contain residue, liquid, or vapors and can be dangerous. Observe all labeled hazard precautions. Do not cut, puncture, or weld while hazard exists. Dispose of according to all federal, state, and local regulations.

**KEEP OUT OF REACH OF CHILDREN.
SEE MSDS FOR MORE INFORMATION.**

Notice to Purchaser: NO WARRANTIES, EXPRESS OR IMPLIED ARE MADE INCLUDING MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE. UNDER NO CIRCUMSTANCES SHALL ITW TACC, A DIVISION OF ILLINOIS TOOL WORKS INC., OR ITS AFFILIATES ("ITW TACC") BE LIABLE FOR ANY LOSS OR DAMAGE ARISING FROM THE PURCHASE, USE, OR INABILITY TO USE THIS PRODUCT, OR FOR ANY SPECIAL, INDIRECT INCIDENTAL, OR CONSEQUENTIAL DAMAGES. THE USER MAY SEND A SAMPLE OF PRODUCT TO ITW TACC FOR TESTING. IF SUCH TESTING PROVES A PRODUCT DEFECT, THE USER'S SOLE AND EXCLUSIVE REMEDY IS EITHER REIMBURSEMENT OF THE PURCHASE PRICE OF THE PRODUCT OR REPLACEMENT OF THE CONTAINER OF PRODUCT. NO FABRICATOR, INSTALLER, DEALER, AGENT OR EMPLOYEE OF ITW TACC HAS THE AUTHORITY TO MODIFY THE OBLIGATIONS OR LIMITATION OF THIS WARRANTY. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state; therefore, some of the limitations stated above may not apply to you. It is to your benefit to save your documentation upon purchase of a product.

Please direct all inquiries regarding performance of this product to:

ITW TACC
56 Air Station Industrial Park
Rockland, MA 02370
Phone 1-800-503-6991 Fax 1-800-231-8222
info@itwtacc.com www.itwtacc.com

Rev. 3/09

